

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations



Printing date: September 27, 2017

Revision: September 27, 2017

1 Identification

- **Product identifier**
- **Trade name:** G-S Hypo Fabric Cement
- **Other product identifiers:** No other identifiers
- **Recommended use and restriction on use**
- **Recommended use:** Adhesives
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
G-S Supplies Inc.
1150 University Avenue, Suite 5
Rochester, NY 14607 USA
Tel (585) 241-2370
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924 (North America)
+1 (813)248-0585 (International)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 2 H225 Highly flammable liquid and vapor.
Eye Irrit. 2A H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.
- **Label elements**
- **GHS label elements**
This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission. GHS labeling is not required per 29CFR1910.1200(b)(5)(v). The labeling below applies to industrial/professional products.
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**

GHS02 GHS07
- **Signal word:** Danger
- **Hazard statements:**
H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
- **Precautionary statements:**
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: September 27, 2017

Revision: September 27, 2017

Trade name: G-S Hypo Fabric Cement

(Cont'd. of page 1)





- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing vapors.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves and eye protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

78-93-3	butanone	 Flam. Liq. 2, H225  Eye Irrit. 2A, H319; STOT SE 3, H336	50-100%
67-64-1	acetone	 Flam. Liq. 2, H225  Eye Irrit. 2A, H319; STOT SE 3, H336	10-25%

· **Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.
 For the wording of the listed Hazard Statements refer to section 16.

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:**

Do not pull solidified product away from the skin.

Clean with water and soap.

If skin irritation continues, consult a doctor.

· **After eye contact:**

Protect unharmed eye.

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: September 27, 2017

Revision: September 27, 2017

Trade name: G-S Hypo Fabric Cement

(Cont'd. of page 2)

- **Most important symptoms and effects, both acute and delayed:**
 - Dizziness
 - Coughing
 - Gastric or intestinal disorders
 - Irritating to eyes.
 - Causes mild skin irritation.
 - Disorientation
- **Danger:**
 - Vapors have narcotic effect.
 - Danger of impaired breathing.
 - Danger of convulsion.
 - Condition may deteriorate with alcohol consumption.
- **Indication of any immediate medical attention and special treatment needed:**
 - If swallowed, gastric irrigation with added, activated carbon.
 - Monitor circulation, possible shock treatment.
 - If necessary oxygen respiration treatment.
 - Medical supervision for at least 48 hours.
 - Later observation for pneumonia and pulmonary edema.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 - Water fog / haze
 - Foam
 - Carbon dioxide
 - Sand
 - Fire-extinguishing powder
- **For safety reasons unsuitable extinguishing agents:** Water stream.
- **Special hazards arising from the substance or mixture**
 - In case of fire, the following can be released:
 - Carbon monoxide (CO)
 - In certain fire conditions, traces of other toxic gases cannot be excluded.
- **Advice for firefighters**
- **Protective equipment:**
 - Wear self-contained respiratory protective device.
 - Wear fully protective suit.
- **Additional information:** Cool endangered containers with water fog.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 - Use respiratory protective device against the effects of fumes/dust/aerosol.
 - Wear protective equipment. Keep unprotected persons away.
 - Ensure adequate ventilation.
 - Keep away from ignition sources.
 - Protect from heat.

(Cont'd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: September 27, 2017

Revision: September 27, 2017

Trade name: G-S Hypo Fabric Cement

(Cont'd. of page 3)

· **Environmental precautions**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Methods and material for containment and cleaning up**

Allow to solidify. Pick up mechanically.
Clean the affected area carefully; suitable cleaners are:
Organic solvent

· **Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

· **Handling**

· **Precautions for safe handling:**

Keep receptacles tightly sealed.
Keep away from heat and direct sunlight.
Use only in well ventilated areas.
Keep out of reach of children.
Avoid contact with the eyes and skin.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Emergency cooling must be available in case of nearby fire.

· **Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and receptacles:**

Avoid storage near extreme heat, ignition sources or open flame.
Store in cool, dry conditions in well sealed receptacles.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.
Store away from oxidizing agents.

· **Further information about storage conditions:**

Storage Temperatures : less than 77 °F / less than 25 °C.

· **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

78-93-3 butanone

PEL (USA)	Long-term value: 590 mg/m ³ , 200 ppm
-----------	--

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: September 27, 2017

Revision: September 27, 2017

Trade name: G-S Hypo Fabric Cement

(Cont'd. of page 4)

REL (USA)	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV (USA)	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI
EL (Canada)	Short-term value: 100 ppm Long-term value: 50 ppm
EV (Canada)	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
LMPE (Mexico)	Short-term value: 300 ppm Long-term value: 200 ppm IBE

67-64-1 acetone

PEL (USA)	Long-term value: 2400 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: 1187 mg/m ³ , 500 ppm Long-term value: 594 mg/m ³ , 250 ppm BEI
EL (Canada)	Short-term value: 500 ppm Long-term value: 250 ppm
EV (Canada)	Short-term value: 750 ppm Long-term value: 500 ppm
LMPE (Mexico)	Short-term value: 750 ppm Long-term value: 500 ppm A4, IBE

Ingredients with biological limit values:

78-93-3 butanone

BEI (USA)	2 mg/L Medium: urine Time: end of shift Parameter: MEK
-----------	---

67-64-1 acetone

BEI (USA)	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----------	--

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.
- Do not inhale gases / fumes / aerosols.

Engineering controls: Provide adequate ventilation.

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: September 27, 2017

Revision: September 27, 2017

Trade name: G-S Hypo Fabric Cement

(Cont'd. of page 5)

- **Breathing equipment:**
Not necessary if room is well-ventilated.
Use suitable respiratory protective device in case of insufficient ventilation.
- **Protection of hands:**



Protective gloves

- **For the permanent contact gloves made of the following materials are suitable:**
Butyl rubber, BR
Nitrile rubber, NBR
Neoprene gloves
- **Eye protection:**



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- **Body protection:**
Not required under normal conditions of use.
Protection may be required for spills.
- **Limitation and supervision of exposure into the environment** No special requirements.
- **Risk management measures** No relevant information available.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

- **Appearance:**
 - **Form:** Liquid
 - **Color:** Clear
- **Odor:** Acetone-like
- **Odor threshold:** Not determined.

- **pH-value:** Not determined.
- **Melting point/Melting range:** Not determined.
- **Boiling point/Boiling range:** 60°C (140 °F)

- **Flash point:** -16°C (3.2 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Auto-ignition temperature:** 465°C (869 °F)

- **Decomposition temperature:** Not determined.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits**
 - **Lower:** 1,8Vol %
 - **Upper:** 13,0Vol %

(Cont'd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: September 27, 2017

Revision: September 27, 2017

Trade name: G-S Hypo Fabric Cement

(Cont'd. of page 6)

· Oxidizing properties:	Non-oxidizing.
· Vapor pressure at 20°C (68 °F):	233hPa (174.8 mm Hg)
· Density:	
Relative density:	0.9
Vapor density:	Not determined.
Evaporation rate:	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Other information	No relevant information available.

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
Avoid temperatures above 77 °F / 25 °C.
- **Possibility of hazardous reactions**
Flammable.
Develops readily flammable gases / fumes.
Reacts with peroxides and other radical forming substances.
Reacts with strong acids and alkali.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
Reacts with oxidizing agents.
- **Conditions to avoid**
Keep ignition sources away - Do not smoke.
Store away from oxidizing agents.
- **Incompatible materials** Oxidizers
- **Hazardous decomposition products**
Carbon monoxide and carbon dioxide
Hydrocarbons

(Cont'd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: September 27, 2017

Revision: September 27, 2017

Trade name: G-S Hypo Fabric Cement

(Cont'd. of page 7)

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

78-93-3 butanone

Oral	LD50	3300 mg/kg (rat)
Dermal	LD50	5000 mg/kg (rabbit)

- **Primary irritant effect:**
- **On the skin:** Causes mild skin irritation.
- **On the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.

· **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

· **NTP (National Toxicology Program):**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

- Ingestion.
- Inhalation.
- Skin contact.
- Eye contact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** May cause drowsiness or dizziness.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** Based on available data, the classification criteria are not met.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity** No relevant information available.
- **Persistence and degradability** The product is partially biodegradable. Significant residuals remain.
- **Bioaccumulative potential:** Does not accumulate in organisms
- **Mobility in soil:** No relevant information available.
- **Ecotoxic effects:**
- **Remark:** Due to mechanical actions of the product (e.g. agglutinations), damages may occur.
- **Additional ecological information**
- **General notes:** Avoid transfer into the environment.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Cont'd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: September 27, 2017

Revision: September 27, 2017

Trade name: G-S Hypo Fabric Cement

(Cont'd. of page 8)

· **Other adverse effects** No relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

· **Uncleaned packagings**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agent:** Solvent naphtha

14 Transport information

· **UN-Number**

· **DOT, IATA**

UN1133 or ID8000

· **ADR, IMDG**

UN1133

· **UN proper shipping name**

· **DOT, IATA**

Adhesives or Consumer Commodity

· **ADR, IMDG**

ADHESIVES

· **Transport hazard class(es)**

· **DOT**



· **Class**

3 or 9

· **Label**

3 or 9

· **ADR**



· **Class**

3 (F1)

· **Label**

3

(Cont'd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: September 27, 2017

Revision: September 27, 2017

Trade name: G-S Hypo Fabric Cement

(Cont'd. of page 9)

· **IMDG**



· **Class** 3
 · **Label** 3

· **IATA**



· **Class** 3 or 9
 · **Label** 3 or 9

· **Packing group**

· **DOT, IATA** II or not applicable
 · **ADR, IMDG** II

· **Environmental hazards**

· **Marine pollutant:** No

· **Special precautions for user**

· **Danger code (Kemler):** Not applicable.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**



Excepted Quantities (EQ)
 EQ Code: E2
 Maximum net quantity per inner packaging: 30 mL
 Maximum net quantity per outer packaging: 500 mL

· **DOT**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

· **ADR**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

(Cont'd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: September 27, 2017

Revision: September 27, 2017

Trade name: G-S Hypo Fabric Cement

(Cont'd. of page 10)

· **IMDG**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

· **IATA**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 0.5 L each / 1 L net.

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

78-93-3 | butanone

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency):**

78-93-3 | butanone

1

67-64-1 | acetone

1

· **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

(Cont'd. on page 12)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: September 27, 2017

Revision: September 27, 2017

Trade name: G-S Hypo Fabric Cement

(Cont'd. of page 11)

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· Canadian Domestic Substances List (DSL):

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision September 27, 2017 / -**· Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bio-accumulable, Toxique

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· SourcesWebsite, European Chemicals Agency (echa.europa.eu)Website, US EPA Substance Registry Services (ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do)Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaassen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com