

## Safety Data Sheet

according to 1907/2006/EC

Printing date: 28 June 2018

Revision: 28 June 2018

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

- Trade name: **G-S Hypo Cement**
- Other means of identification: No other identifiers

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

- Sector of Use SU21 Consumer uses: Private households / general public / consumers
- Application of the substance / the mixture: Adhesives
- Uses advised against: No further relevant information available.

#### 1.3 Details of the supplier of the Safety Data Sheet

- Manufacturer/Supplier:  
G-S Supplies Inc.  
1150 University Avenue, Suite 5  
Rochester, NY 14607 USA  
Tel (585) 241-2370

#### 1.4 Emergency telephone number:

- ChemTel Inc.  
(800)255-3924 (North America)  
+1 (813)248-0585 (International)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

- |                   |           |  |
|-------------------|-----------|--|
| Flam. Liq. 2      | H225      | Highly flammable liquid and vapour.                                  |
| Skin Irrit. 2     | H315      | Causes skin irritation.  |
| Eye Irrit. 2      | H319      | Causes serious eye irritation.                                       |
| STOT SE 3         | H335-H336 | May cause respiratory irritation. May cause drowsiness or dizziness. |
| Aquatic Acute 1   | H400      | Very toxic to aquatic life.  |
| Aquatic Chronic 1 | H410      | Very toxic to aquatic life with long lasting effects.                |

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the CLP regulation.

##### Hazard pictograms



GHS02 GHS07 GHS09

##### Signal word Danger

##### Hazard-determining components of labelling:

- heptane
- m-xylene
- p-xylene
- o-xylene

##### Hazard statements

(Cont'd. on page 2)

## Safety Data Sheet

according to 1907/2006/EC

Printing date: 28 June 2018

Revision: 28 June 2018

**Trade name: G-S Hypo Cement**

(Cont'd. from page 1)

- H225 Highly flammable liquid and vapour.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.  
 H410 Very toxic to aquatic life with long lasting effects.

**Precautionary statements**

- P102 Keep out of reach of children.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P261 Avoid breathing vapours.  
 P264 Wash thoroughly after handling.  
 P273 Avoid release to the environment.  
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
 P403+P235 Store in a well-ventilated place. Keep cool.

· **2.3 Other hazards** There are no other hazards not otherwise classified that have been identified.

**Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**3.2 Mixtures**
**Components:**

CAS: 142-82-5 EINECS: 205-563-8 Index number: 601-008-00-2 Reg.nr.: 01-2119457603-38-XXXX	heptane ⚠ Flam. Liq. 2, H225 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	20-40%
CAS: 108-38-3 EINECS: 203-576-3 Index number: 601-022-00-9 Reg.nr.: 01-2119484621-37-XXXX	m-xylene ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	10-20%
CAS: 106-42-3 EINECS: 203-396-5 Index number: 601-022-00-9 Reg.nr.: 01-2119484661-33-XXXX	p-xylene ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	5-10%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35-XXXX	ethylbenzene ⚠ Flam. Liq. 2, H225 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H332	5-10%
CAS: 95-47-6 EINECS: 202-422-2 Index number: 601-022-00-9 Reg.nr.: 01-2119485822-30-XXXX	o-xylene ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2,	1-5%

(Cont'd. on page 3)

**Safety Data Sheet**  
according to 1907/2006/EC

Printing date: 28 June 2018

Revision: 28 June 2018

**Trade name: G-S Hypo Cement**

(Cont'd. from page 2)

	H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	
--	--	--

· **Additional information:** For the wording of the listed Hazard Statements refer to section 16.

**SECTION 4: First aid measures**

· **4.1 Description of first aid measures**

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· **After skin contact:**

Do not pull solidified product off the skin.  
Clean with water and soap.  
If skin irritation continues, consult a doctor.

· **After eye contact:**

Protect unharmed eye.  
Remove contact lenses if worn, if possible.  
Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.  
Do not induce vomiting; call for medical help immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

Headache  
Coughing  
Dizziness  
Breathing difficulty  
Disorientation

· **Hazards:**

Danger of impaired breathing.  
Danger of cerebral oedema.  
Danger of convulsion.

· **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation with added, activated carbon.  
Monitor circulation, possible shock treatment.  
If necessary oxygen respiration treatment.  
Medical supervision for at least 48 hours.  
Later observation for pneumonia and pulmonary oedema.

**SECTION 5: Firefighting measures**

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

Water haze or fog  
Foam  
Fire-extinguishing powder  
Carbon dioxide  
Sand

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

(Cont'd. on page 4)

## Safety Data Sheet

according to 1907/2006/EC

Printing date: 28 June 2018

Revision: 28 June 2018

**Trade name: G-S Hypo Cement**

(Cont'd. from page 3)

**5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

**5.3 Advice for firefighters****Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

**Additional information:** Cool endangered receptacles with water fog or haze.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Protect from heat.

**6.2 Environmental precautions**

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

**6.3 Methods and material for containment and cleaning up**

Allow to solidify. Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Clean the affected area carefully; suitable cleaners are:

Organic solvent

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Open and handle receptacle with care.

Keep out of reach of children.

Avoid contact with the eyes and skin.

Use only in well ventilated areas.

Keep receptacles tightly sealed.

Keep away from heat and direct sunlight.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Emergency cooling must be available in case of nearby fire.

**7.2 Conditions for safe storage, including any incompatibilities****Requirements to be met by storerooms and receptacles:**

Avoid storage near extreme heat, ignition sources or open flame.

(Cont'd. on page 5)

**Safety Data Sheet**  
according to 1907/2006/EC

Printing date: 28 June 2018

Revision: 28 June 2018

**Trade name: G-S Hypo Cement**

(Cont'd. from page 4)

- Store in cool, dry conditions in well sealed receptacles.
- **Information about storage in one common storage facility:**  
Store away from foodstuffs.  
Store away from oxidising agents.
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**142-82-5 heptane**

IOELV (EU)	Long-term value: 2085 mg/m <sup>3</sup> , 500 ppm
WEL (Great Britain)	Long-term value: 2085 mg/m <sup>3</sup> , 500 ppm
OEL (Ireland)	Long-term value: 2085 mg/m <sup>3</sup> , 500 ppm IOELV

**108-38-3 m-xylene**

IOELV (EU)	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm Long-term value: 221 mg/m <sup>3</sup> , 50 ppm Skin
WEL (Great Britain)	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
OEL (Ireland)	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm Long-term value: 221 mg/m <sup>3</sup> , 50 ppm Sk, IOELV

**106-42-3 p-xylene**

IOELV (EU)	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm Long-term value: 221 mg/m <sup>3</sup> , 50 ppm Skin
WEL (Great Britain)	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
OEL (Ireland)	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm Long-term value: 221 mg/m <sup>3</sup> , 50 ppm Sk, IOELV

**100-41-4 ethylbenzene**

IOELV (EU)	Short-term value: 884 mg/m <sup>3</sup> , 200 ppm Long-term value: 442 mg/m <sup>3</sup> , 100 ppm Skin
WEL (Great Britain)	Short-term value: 552 mg/m <sup>3</sup> , 125 ppm Long-term value: 441 mg/m <sup>3</sup> , 100 ppm Sk
OEL (Ireland)	Short-term value: 884 mg/m <sup>3</sup> , 200 ppm Long-term value: 442 mg/m <sup>3</sup> , 100 ppm Sk, IOELV

(Cont'd. on page 6)

## Safety Data Sheet

according to 1907/2006/EC

Printing date: 28 June 2018

Revision: 28 June 2018

**Trade name: G-S Hypo Cement**

(Cont'd. from page 5)

**95-47-6 o-xylene**

IOELV (EU)	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm Long-term value: 221 mg/m <sup>3</sup> , 50 ppm Skin
WEL (Great Britain)	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
OEL (Ireland)	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm Long-term value: 221 mg/m <sup>3</sup> , 50 ppm Sk, IOELV

- **DNELs:** No further relevant information available.
- **PNECs:** No further relevant information available.

**Ingredients with biological limit values:**
**108-38-3 m-xylene**

BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
----------------------	--

**106-42-3 p-xylene**

BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
----------------------	--

**95-47-6 o-xylene**

BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
----------------------	--

**8.2 Exposure controls**
**General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.

**Respiratory protection:**

- Not necessary if room is well-ventilated.
- Use suitable respiratory protective device in case of insufficient ventilation.

**Protection of hands:**


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

**For the permanent contact gloves made of the following materials are suitable:**

- Nitrile rubber, NBR
- Butyl rubber, BR

(Cont'd. on page 7)

## Safety Data Sheet

according to 1907/2006/EC

Printing date: 28 June 2018

Revision: 28 June 2018

**Trade name: G-S Hypo Cement**

(Cont'd. from page 6)

- **For the permanent contact of a maximum of 15 minutes, gloves made of the following materials are suitable:**  
Natural rubber, NR
- **Not suitable are gloves made of the following materials:** PVA gloves
- **Eye protection:**



Safety glasses

- **Body protection:** Protective work clothing
- **Limitation and supervision of exposure into the environment:**  
No further relevant information available.
- **Risk management measures:** No further relevant information available.

### SECTION 9: Physical and chemical properties

#### · 9.1 Information on basic physical and chemical properties

##### · Appearance

- |                           |                 |
|---------------------------|-----------------|
| · <b>Form:</b>            | Liquid          |
| · <b>Colour:</b>          | Transparent     |
| · <b>Odour:</b>           | Aromatic        |
| · <b>Odour threshold:</b> | Not determined. |

- |   |                 |
|---|-----------------|
| · <b>pH-value:</b>                                | Not determined. |
| · <b>Melting point/freezing point:</b>            | Not determined. |
| · <b>Initial boiling point and boiling range:</b> | 98 °C           |

- |                       |       |
|-----------------------|-------|
| · <b>Flash point:</b> | 11 °C |
|-----------------------|-------|

- |                                     |                 |
|-------------------------------------|-----------------|
| · <b>Flammability (solid, gas):</b> | Not applicable. |
|-------------------------------------|-----------------|

- |  |        |
|--|--------|
| · <b>Auto/Self-ignition temperature:</b> | 215 °C |
|--|--------|

- |                                     |                 |
|-------------------------------------|-----------------|
| · <b>Decomposition temperature:</b> | Not determined. |
|-------------------------------------|-----------------|

- |                                |   |
|--------------------------------|---|
| · <b>Explosive properties:</b> | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
|--------------------------------|---|

##### · Explosion limits

- |                 |           |
|-----------------|-----------|
| · <b>Lower:</b> | 1,1 Vol % |
| · <b>Upper:</b> | 6,7 Vol % |

- |                               |                |
|-------------------------------|----------------|
| · <b>Oxidising properties</b> | Non-oxidising. |
|-------------------------------|----------------|

- |                                    |        |
|------------------------------------|--------|
| · <b>Vapour pressure at 20 °C:</b> | 48 hPa |
|------------------------------------|--------|

##### · Density:

- |                            |                 |
|----------------------------|-----------------|
| · <b>Relative density:</b> | 1,01            |
| · <b>Vapour density:</b>   | Not determined. |
| · <b>Evaporation rate:</b> | Not determined. |

- |  |                                   |
|--|-----------------------------------|
| · <b>Solubility in / Miscibility with water:</b> | Not miscible or difficult to mix. |
|--|-----------------------------------|

(Cont'd. on page 8)

## Safety Data Sheet

according to 1907/2006/EC

Printing date: 28 June 2018

Revision: 28 June 2018

**Trade name: G-S Hypo Cement**

(Cont'd. from page 7)

- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity**
  - Dynamic:** Not determined.
  - Kinematic at 40 °C:** >21 mm<sup>2</sup>/sec
- **9.2 Other information** No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**  
Reacts with strong acids.  
Highly flammable liquid and vapour.  
Forms flammable gases/fumes.  
Reacts with oxidising agents.  
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.  
Reacts with peroxides and other radical forming substances.
- **10.4 Conditions to avoid** Excessive heat.
- **10.5 Incompatible materials** Oxidisers
- **10.6 Hazardous decomposition products**  
Carbon monoxide and carbon dioxide  
Hydrocarbons

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:**
- 100-41-4 ethylbenzene**
- Oral | LD50 | 3500 mg/kg (rat)
- **Primary irritant effect**
- **Skin corrosion/irritation:**  
Causes skin irritation.
- **Serious eye damage/irritation:**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation:** Based on available data, the classification criteria are not met.
- **IARC (International Agency for Research on Cancer):**
- 100-41-4 | ethylbenzene | 2B
- **Probable routes of exposure:**  
Ingestion.  
Inhalation.  
Eye contact.

(Cont'd. on page 9)



## Safety Data Sheet

according to 1907/2006/EC

Printing date: 28 June 2018

Revision: 28 June 2018

**Trade name: G-S Hypo Cement**

(Cont'd. from page 8)

Skin contact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:**  
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** Toxic to aquatic life with long lasting effects.
- **12.2 Persistence and degradability**  
The product is partially biodegradable. Significant residuals remain.
- **12.3 Bioaccumulative potential**  
Due to the distribution coefficient n-octanol/water an accumulation in organisms is not expected.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Very toxic for fish
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Solvent naphtha

### SECTION 14: Transport information

- **14.1 UN-Number**
- **DOT, IATA** UN1133 or ID8000
- **ADR, IMDG** UN1133

(Cont'd. on page 10)

**Safety Data Sheet**  
according to 1907/2006/EC

Printing date: 28 June 2018

Revision: 28 June 2018

**Trade name: G-S Hypo Cement**

(Cont'd. from page 9)

**14.2 UN proper shipping name**

· DOT, ADR, IMDG  
· IATA

ADHESIVES  
Adhesives or Consumer Commodity

**14.3 Transport hazard class(es)**

· DOT



· Class 3 or 9  
· Label 3 or 9

· ADR



· Class 3 (F1)  
· Label 3

· IMDG



· Class 3  
· Label 3

· IATA



· Class 3 or 9  
· Label 3 or 9

**14.4 Packing group**

· DOT, IATA II or not applicable  
· ADR, IMDG II

**14.5 Environmental hazards:**

Product contains environmentally hazardous substances: heptane

· Marine pollutant:



Yes

**14.6 Special precautions for user**

· Danger code (Kemler): 33  
· EMS Number: F-E,S-D

(Cont'd. on page 11)

**Safety Data Sheet**  
according to 1907/2006/EC

Printing date: 28 June 2018

Revision: 28 June 2018

**Trade name: G-S Hypo Cement**

(Cont'd. from page 10)

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.

· **Transport/Additional information:**



Excepted Quantities (EQ)  
EQ Code: E2  
Maximum net quantity per inner packaging: 30 mL  
Maximum net quantity per outer packaging: 500 mL

· **DOT**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

Labeling as a Marine Pollutant is only required for bulk single package shipments. Bulk packaging consists of a maximum capacity of greater than 450 L (119 gallons) for a liquid and a maximum net mass greater than 400 kg (882 pounds) for a solid. (See 171.4(c))

· **ADR**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 5.2.1.8.1)

· **IMDG**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 2.10.2.7)

· **IATA**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 0,5 L each / 1 L net.

**SECTION 15: Regulatory information**

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **IARC (International Agency for Research on Cancer)**

(Cont'd. on page 12)

## Safety Data Sheet

according to 1907/2006/EC

Printing date: 28 June 2018

Revision: 28 June 2018

**Trade name: G-S Hypo Cement**

(Cont'd. from page 11)

100-41-4 ethylbenzene

2B

· **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients are listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **Sources**

Website, European Chemicals Agency ([echa.europa.eu](http://echa.europa.eu))

Website, US EPA Substance Registry Services ([ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do](http://ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do))

(Cont'd. on page 13)

## Safety Data Sheet

according to 1907/2006/EC

Printing date: 28 June 2018

Revision: 28 June 2018

**Trade name: G-S Hypo Cement**

(Cont'd. from page 12)

Website, Chemical Abstracts Registry, American Chemical Society ([www.cas.org](http://www.cas.org))

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: [www.chemtelinc.com](http://www.chemtelinc.com)