

G-S SUPPLIES, INC.

REFERENCE LIST

MINIMUM ORDER QUANTITY: THREE (3) DOZEN, 1/4 DOZEN PER SIZE
Some sizes notes below are not stock sizes. Please call for availability and quote.

GAUGE AND INSTRUMENT BRAND NAMES AND CORRESPONDING G-S WINDOWS

| GAUGE BRAND NAME AND MODEL | G-S ITEM ID | INCHES | MILLIMETERS |
|--|-------------|--------|-------------|
| ALINA M49, M50, K53 | W106 | 3.150 | 80.0 |
| ALINA 88 | W19-1/2 | .9875 | 25.0 |
| ALINA 41-132-044 | W18-1/2 | .9625 | 24.4 |
| ALINA 41-226-006 | W41-1/2 | 1.5375 | 39.0 |
| AMES 25 | *PKH45-1/2 | 1.6375 | 41.6 |
| AMES 27 | W56 | 1.900 | 48.0 |
| AMES 27 | *PKH54 | 1.850 | 47.0 |
| AMES 55 | W56 | 1.900 | 48.2 |
| AMES 100 | AMES 100 | 1.606 | 40.8 |
| AMES 200 (OLD) | AMES 200 | 2.166 | 55.0 |
| AMES 200 (NEW) | W66 | 2.150 | 54.6 |
| AMES 300 (OLD) | AMES 300 | 2.669 | 67.8 |
| AMES 300 (NEW) | W86-1/2 | 2.6625 | 67.6 |
| AMES 400 | AMES 400 | 3.500 | 88.9 |
| AMES 516-T2 | *PKH38-1/2 | 1.4625 | 37.1 |
| BROWN & SHARPE BESTEST | W18-1/2 | .9625 | 24.4 |
| BROWN & SHARPE 578-1, 579-1 | *PKH38-1/2 | 1.4625 | 37.1 |
| BROWN & SHARPE 579-2, 579-3, 579-4 | *BS 579-2 | 1.392 | 35.4 |
| BROWN & SHARPE 6032 | W24 | 1.100 | 27.9 |
| BROWN & SHARPE 7029-8 | W24 | 1.100 | 27.9 |
| BROWN & SHARPE 7030 | W24 | 1.100 | 27.9 |
| BROWN & SHARPE 7031 | W39-1/2 | 1.4875 | 37.7 |
| BROWN & SHARPE 7031-1 | W24 | 1.100 | 27.9 |
| BROWN & SHARPE 7030-3 | *BS 7030-3 | 1.088 | 27.6 |
| BROWN & SHARPE 7031-3 | *BS 7031-3 | 1.466 | 37.2 |
| BROWN & SHARPE 7031-107 | W24 | 1.100 | 27.9 |
| BROWN & SHARPE 7031-202 | W39-1/2 | 1.4875 | 37.7 |
| BROWN & SHARPE 7039 | W39 | 1.475 | 37.4 |
| BROWN & SHARPE 8100 | W45 | 1.625 | 41.2 |
| BROWN & SHARPE 8200 | W66-1/2 | 2.1625 | 54.9 |
| BROWN & SHARPE 8300 | W86 | 2.650 | 67.3 |
| CHICAGO DIAL 1-25-17 | W42-1/2 | 1.562 | 39.7 |
| CHICAGO DIAL 2-25-17 | W64 | 2.100 | 53.3 |
| CHICAGO DIAL 3-25-17 | W85-1/2 | 2.637 | 67.0 |
| CHICAGO DIAL 4-25-17 (In Lots of 500 Only) | W118-1/2 | 3.467 | 88.1 |
| COMPACT | W19-1/2 | .9875 | 25.0 |
| COMPTOR P2 AMPLIFIER | W86-1/2 | 2.6625 | 67.6 |
| CYCLE STOP WATCH | PKH57 | 1.925 | 48.9 |
| FEDERAL "A" | W25 | 1.125 | 28.5 |
| FEDERAL "B" | W43 | 1.575 | 40.0 |
| FEDERAL "C", "G", "J", "W" | W64-1/2 | 2.112 | 53.6 |
| FEDERAL "D" | W83-1/2 | 2.5875 | 65.7 |
| FEDERAL "E" (IN LOTS OF 500 ONLY) | FED "E" | 3.500 | 88.9 |
| FEDERAL TESTMASTER LM OR LT | W41-1/2 | 1.5375 | 39.0 |
| FEDERAL TESTMASTER LT-80 | W56 | 1.900 | 48.2 |
| FEDERAL TESTMASTER M | W21 | 1.025 | 26.0 |
| FEDERAL TESTMASTER T-80 | W34-1/2 | 1.3625 | 34.6 |
| FOWLER 212-02 7-10-12 | W56 | 1.900 | 48.2 |
| FOWLER-GIROD | W24 | 1.100 | 27.9 |
| FOWLER-GIROD 02 008 015 | W39-1/2 | 1.4875 | 37.7 |
| G.I. CRYSTALS | GI CRYSTAL | 1.189 | 30.2 |
| GEM 222 | ST-7112 | .922 | 23.4 |
| GEM 333 | *PK33 | 1.325 | 33.6 |
| GEM 400 | *PK22-1/2 | 1.0625 | 26.9 |
| GENEVA | *PKH56-1/2 | 1.9125 | 48.5 |
| GIROD (FOWLER) | W24 | 1.100 | 27.9 |
| GIROD (FOWLER) 02 008 015 | W39-1/2 | 1.4875 | 37.7 |
| HELIOS 10" CALIPER | W41 | 1.525 | 38.7 |

REFERENCE LIST

GAUGE AND INSTRUMENT BRAND NAMES AND CORRESPONDING G-S WINDOWS

| GAUGE BRAND NAME AND MODEL | G-S ITEM ID | INCHES | MILLIMETERS |
|--|------------------|----------------|-------------|
| HELIOS 6" DIAL CALIPER | W30 | 1.250 | 31.7 |
| INTERRAPID #91-B2, 92, 101, 310-B2 | *PK24 | 1.100 | 27.9 |
| INTERRAPID #102, 310-B15 | *INT-102 | 1.417 | 36.0 |
| INTERRAPID #310-B1 | W35 | 1.375 | 34.9 |
| LUFKIN 299 | L299 | 1.400 | 35.6 |
| MAHR 15.56.6 | W65-1/2 | 2.1375 | 54.3 |
| MICROMASTER | *PK19 | .975 | 24.7 |
| MITUTOYO 101032 | W63-1/2 | 2.087 | 53.0 |
| MITUTOYO 101207 | W40 | 1.499 | 38.1 |
| MITUTOYO 101579 | W34-1/2 | 1.3625 | 34.6 |
| MITUTOYO 101601 | W45-1/2 | 1.625 | 41.2 |
| MITUTOYO 103146 | W28 | 1.200 | 30.4 |
| MITUTOYO 141776 | W38-1/2 | 1.4625 | 37.15 |
| MITUTOYO 900706 | W94 | 2.850 | 72.4 |
| NSK | *PK33 | 1.325 | 33.6 |
| OLDAK | *PKH55-1/2 | 1.8875 | 47.9 |
| OLDAK A.L.S.18 | *PKH57-1/2 | 1.9375 | 49.2 |
| PARVUS | W41-1/2 | 1.5375 | 39.0 |
| PARVUS SMALL 1" DIAMETER | W19-1/2 | .9875 | 25.0 |
| PEACOCK 120001 | W65 | 2.125 | 54.0 |
| PEARSON | W22-1/2 | 1.0625 | 26.9 |
| PHASE II 1" INDICATOR MOD. 900-102 | W66-1/2 | 2.162 | 54.9 |
| SCHERR-TUMICO (NSK) | *PK33 | 1.325 | 33.6 |
| SEARS (NSK) | *PK33 | 1.325 | 33.6 |
| SPOT-ON | *PK20-1/2 | 1.0125 | 25.7 |
| STANDARD 045 MIDGET (OLD) | W21-1/2 | 1.0375 | 26.3 |
| STANDARD X1-33026 #1 CHECKMASTER | W44-1/2 | 1.6125 | 40.9 |
| STANDARD 33050 (#1 OLD) | W41-1/2 | 1.5375 | 39.0 |
| STANDARD X1-33126 #1 AGD | W47 | 1.675 | 42.5 |
| STANDARD 33131 #2041 | W66 / W66-1/2 | 2.150 / 2.1625 | 54.6 / 54.9 |
| STANDARD X1-33163 #2 AGD | W66 | 2.150 | 54.6 |
| STANDARD X1-33263 #3 AGD | W90-1/2 | 2.7625 | 70.2 |
| STANDARD X1-33755 MIDGET & CHECKMASTER | W22 | 1.050 | 26.6 |
| STARRETT 196 P/N #5798 | LMG 35.8 or 35.9 | 1.412 | 35.8/35.9 |
| STARRETT 25 P/N #6622 | W64 | 2.100 | 53.3 |
| STARRETT 81 P/N #6846 | W43 | 1.575 | 40.0 |
| STARRETT 81 P/N #6863 | W44 | 1.600 | 40.6 |
| STARRETT 655 P/N #6886 | W84 | 2.600 | 66.0 |
| STARRETT 656 P/N #6908 (In Lots of 500 Only) | 2216 | 3.455 | 87.8 |
| STARRETT 7112 (OLD) | ST-7112 Old | .922 | 23.4 |
| STARRETT 7112 (NEW) - 2228-B | PHD 16-3/4 | .922 | 23.4 |
| STARRETT 711-D10 P/N #7113 | *PKH54 | 1.850 | 47.0 |
| STARRETT 1010 P/N #7486 | W45 | 1.625 | 41.2 |
| STARRETT 25 P/N #11211 | W65 | 2.125 | 54.0 |
| STARRETT 711-T1 P/N #11727 | W20-1/2 | 1.0125 | 25.7 |
| STARRETT 120 P/N #19043 | W38 | 1.450 | 36.8 |
| STARRETT 120 P/N #19043 | W38 | 1.450 | 36.8 |
| STARRETT 196 P/N 91525 | W38 | 1.450 | 36.8 |
| STARRETT 80 P/N #25084 | W26 | 1.150 | 29.2 |
| TECKLOCK 1" | *PKH60 | 2.000 | 50.8 |
| TESA 20-101 1" BS7030-3 | *BS 7030-3 | 1.088 | 27.6 |
| TESA 20-103 1-1/2" BS7031-3 | *BS 7031-3 | 1.466 | 37.2 |
| TESA | W19-1/2 | .9875 | 25.0 |
| TUMICO 2-1/4 | W64-1/2 | 2.1375 | 54.3 |
| TUMICO AL13 | W97 | 2.925 | 74.3 |
| VERDICT | W19 | .975 | 24.7 |
| WRIGHT RESPIROMETER-Hand clearance adaptation needed | W71 | 2.275 | 57.8 |
| WRIGHT RESPIROMETER Mark 8, 14, Haloscale Infanta | PKH 37-1/2 | 1.4375 | 36.5 |
| YUASA | W64-1/2 | 2.112 | 53.6 |

*Use Window (Crystal) Lift or Fitting Machine